



DOMESTIC CRANKSHAFTS



Part Number	Former P/N	Description	Stroke	Main Journal Diameter	Rod Pin Diameter	Minimum Rod Length	Flange	Bob Weight (Grams)	Weight (Lbs)	Foot note
CHRYSLER 440										
007HAG425	440-4250JC6F	Forged Crankshaft	4.250	2.75"	2.200	6.760	6	2350	71	B
FORD 302										
011DAI340	302-3400GB6F	Forged Crankshaft	3.400	302	2.100	5.400"	6F	1750	47	
FORD 351 (*Uses Windsor snout)										
011EAD400*	351-4000HB6F-S	Forged Crankshaft	4.000	2.75"	2.100	6.200"	6F	1850	61	C, S
011FAD400	351-4000KB6F-S	Forged Crankshaft	4.000	3.00"	2.100	6.200"	6F	1900	61	S, W



SPORT COMPACT CRANKSHAFTS

Part Number	Former P/N	Description	Stroke	Main Journal Diameter	Rod Pin Diameter	Minimum Rod Length	Flange	Bob Weight (Grams)	Weight (Lbs)	Foot note
HONDA K SERIES										
015HBS920	H920K24S	Billet Crankshaft	92.000	55.00	GSR		8		Call	
015HBS103	H1030K24S	Billet Crankshaft	103.000	55.00	GSR		8		Call	
MITSUBISHI 4G63 7 BOLT										
032BCJ880	M8804G63-L	Billet Crankshaft	88.000	57.00	45		7		30	L
032BCJ940	M9404G63-L	Billet Crankshaft	94.000	57.00	45		7		30	L
032BCJ100	M10004G63-L	Billet Crankshaft	100.000	57.00	45		7		30	L
MITSUBISHI 4B11T										
032DCK980	M980B11S	Billet Crankshaft	98.000	52	52		7		Call	
NISSAN SR20										
033ECS920	N920SR20	Billet Crankshaft	92.000	55	48		8		42	
SUBARU EJ SERIES										
039ADD750	S750EJ20D	Dual Thrust Billet Crankshaft	75.000	60	52		8		21	
039ADD790	S790EJ25D	Dual Thrust Billet Crankshaft	79.000	60	52		8		21	
039ADD830	S830EJ25D	Dual Thrust Billet Crankshaft	83.000	60	52		8		21	
VOLKSWAGEN										
043BDQ928	VW928ABA-L	Billet Crankshaft	92.800	54	47.8		6		33	L
VOLVO										
044ADV860	V860B230-L	Billet Crankshaft	86.000	63	49		8		41	L

Key

Flange: 6: 6 Bolt / 6C: 6 Chevy / 6F: 6 Ford / 6P: 6 - Pre '71 / 8: 8 Bolt

Footnotes: B: BBC Rod Journals / C: Cleveland Mains / L: Lightweight / S: SBC Rod Journals / W: Windsor Mains
24: 24T Reluctor / 58: 58T Reluctor



Part Number	Former P/N	Length	Housing Bore	Pin Diameter	BE Width	PE Width	Bolt Size	Bolt P/N	Gram Weight	Foot note
LANCIA DELTA 16V H-Beam Design with ARP 2000 Bolts										
010ED17145	KE-FLH5709AHGB4-A	145.0mm	53.820	22mm	25.700	25.700	3/8"	DD	569	
010ED17145S	KE-FLH5709AHGB1-A	145.0mm	53.820	22mm	25.700	25.700	3/8"	DD	569	S
MAZDA B6-ZE / BP H-Beam Design with ARP 2000 Bolts										
028CC14133	ZH5234ACCB4-A	133.0mm	48.009	20mm	21.840	21.840	3/8"	CC	490	
028CC14133S	ZH5234ACCB1-A	133.0mm	48.009	20mm	21.840	21.840	3/8"	CC	490	S
MAZDA FS-DE H-Beam Design with ARP 2000 Bolts										
028CD12135	ZH5315AEAB4-A	135.0mm	51.000	19mm	21.790	21.790	3/8"	DD	530	
028CD12135S	ZH5315AWAB1-A	135.0mm	51.000	19mm	21.790	21.790	3/8"	DD	530	S
MAZDA KL 2.5L H-Beam Design with ARP 2000 Bolts										
028CE16138	FH5426AKFB6-A	137.8mm	56.070	21mm	21.230	21.230	3/8"	DD	584	
028CE16138S	FH5426AKFB1-A	137.8mm	56.070	21mm	21.230	21.230	3/8"	DD	584	S
MAZDA L 2.3L DISI H-Beam Design with ARP 2000 Bolts										
028CF17151	ZH5927AJGB4-A	150.5mm	55.008	22mm	21.790	21.790	3/8"	DD	555	
028CF17151S	ZH5927AJGB1-A	150.5mm	55.008	22mm	21.790	21.790	3/8"	DD	555	S
028CF19151	ZH5927AJAFB4-A	150.5mm	55.008	22.5mm	21.790	21.790	3/8"	DD	552	
028CF19151S	ZH5927AJAFB1-A	150.5mm	55.008	22.5mm	21.790	21.790	3/8"	DD	552	S
MG CAR COMPANY H-Beam Design with ARP 2000 Bolts										
030CH15650	MGH6500BKEB4-A	6.500"	51.340	20.630	25.400	25.400	3/8"	DD	626	
030CH15650S	MGH6500BKEB1-A	6.500"	51.340	20.630	25.400	25.400	3/8"	DD	626	S
MITSUBISHI 4G63 - 6 BOLT H-Beam Design with ARP 2000 Bolts										
032CI16150	MH5906ACFB-L4-A	150.0mm	48.009	21mm	28.300	28.300	3/8"	CC	533	L
032CI16150S	MH5906ACFB-L1-A	150.0mm	48.009	21mm	28.300	28.300	3/8"	CC	533	L, S
MITSUBISHI 4G63 - 7 BOLT H-Beam Design with ARP 2000 Bolts										
032CJ17150	MH5906ACGB4-A	150.0mm	48.009	22mm	26.370	22.860	3/8"	CC	581	
032CJ17150S	MH5906ACGB1-A	150.0mm	48.009	22mm	26.370	22.860	3/8"	CC	581	S
032CJ17162	MH6378ACGB4-A	162.0mm	48.009	22mm	26.370	22.860	3/8"	DD	588	
032CJ17162S	MH6378ACGB1-A	162.0mm	48.009	22mm	26.370	22.860	3/8"	DD	588	S
MITSUBISHI 4B11T H-Beam Design with ARP 2000 Bolts										
032CK21144	MH5658AJJB4-A	143.7mm	55.005	23mm	21.870	19.860	3/8"	DD	540	
032CK21144S	MH5658AJJB1-A	143.7mm	55.005	23mm	21.870	19.860	3/8"	DD	540	S
MITSUBISHI 4G93 H-Beam Design with ARP 2000 Bolts										
032CN12133	MH5250ACAB4-A	133.35mm	47.752	19mm	21.840	21.800	3/8"	DD	483	
032CN12133S	MH5250ACAB1-A	133.35mm	47.752	19mm	21.840	21.800	3/8"	DD	483	S

Key

Bolt P/N: AA: BT51500-2 / BB: BT51500-4 / CC: BT61501-2 / DD: BT61601-2 / EE: BT71401-2 / FF: BT71601-2 / GG: BT71801-2
Footnotes: L: Lightweight / S: Single Rod Part Number / 1: 2008-14 Gen 2 / 2: 1997-07 Gen 1 / 3: 84mm+ Bore Only