

Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Meas.	Guide Min	Max	Current Part No.	Old Part No.
<b>HONDA S2000 F22C 2.2L GOLD SERIES - FOR USE IN FACTORY FRM (FIBER REINFORCED MATRIX) CYLINDERS ONLY</b>													
1.2, 1.2, 2.8mm Performance Ring Set Included, Designed for Aftermarket Rods													
CR calculated at 1.0mm above deck and 0.76mm head gasket thickness							<b>54cc</b>						
87.00mm	90.7mm	149.65mm	30mm	23mm	9.0cc	331	13.4	4032	0.375	0.0006	0.0014	929986125	* S2K181425X09**
87.10mm						332	13.4					929986129	* S2K181429X09**
87.25mm						334	13.4					929986135	* S2K181435X09**
<b>87.00mm</b>					<b>-11.0cc</b>	<b>303</b>	<b>9.5</b>	<b>2618</b>	<b>0.375</b>	<b>0.0016</b>	<b>0.0024</b>	<b>929986425</b>	* S2K181425P11*
87.25mm						306	9.5					929986435	* S2K181435P11*

\*PowerPak Plus 2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications

\*\*Hard Anodized Top Ring Groove For Extreme Duty Applications

**HYUNDAI THETA L-4 TURBO 2.0L**

1.2, 1.2, 2.8mm Performance Ring Set Included													
CR calculated at 0.5mm below deck and 4.69cc gasket volume							<b>50.5cc</b>						
86.00mm	86.0mm	146mm	30mm	22mm	-11.4cc	300	8.5	2618	0.260	0.0025	0.0033	929960585	HYU1814385114

**HYUNDAI LAMBDA V-6 TURBO 3.8L**

1.2, 1.2, 2.8mm Performance Ring Set Included													
CR calculated at 0.5mm below deck and 4.69cc gasket volume							<b>67cc</b>						
96.00mm	87.0mm	149.5mm	31.47mm	22mm	-22.8cc	393	9.0	4032	0.235	0.0016	0.0024	929959680	HYU239780123

**MAZDA MZR 2.3L DISI**

1.2, 1.2, 2.8mm Performance Ring Set Included													
CR calculated at 0.5mm below deck and 4.69cc gasket volume							<b>44cc</b>						
87.50mm	94.0mm	150.622mm	32.87mm	22.5mm	-15.2cc	342	9.5	2618	0.250	0.0021	0.0029	197723845	*
88.00mm						349	9.6					197723865	*
87.50mm	94.0mm	150.622mm	32.87mm	22.5mm	-15.2cc	334	9.5	4032	0.250	0.0016	0.0024	197786145	**
88.00mm						340	9.6					197786165	**

\*PowerPak Plus 2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications.

\*\*Hard Anodized Top Ring Groove

**MITSUBISHI 4G63 2.0L 88-92 ECLIPSE**

1.2, 1.2, 2.8mm Performance Ring Set Included													
CR calculated at 0.3mm below deck and 1.3mm head gasket thickness							<b>47cc</b>						
85.50mm	88.0mm	150mm	34.7mm	21mm	-10.0cc	313	8.7	4032	0.236	0.0016	0.0024	929981966	MIT367366H10
86.00mm						319	8.7					929981986	MIT367385H10

**MITSUBISHI 4G63 2.0L 93-02 ECLIPSE 03-09 LANCER EVO**

1.2, 1.2, 2.8mm Performance Ring Set Included													
CR calculated at 0.3mm below deck and 1.3mm head gasket thickness							<b>47cc</b>						
85.00mm	88.0mm	150mm	34.7mm	22mm	-10.0cc	305	8.6	4032	0.236	0.0016	0.0024	930130046	EVO367346H10
85.50mm						311	8.7					930130066	EVO367366H10
86.00mm						318	8.7					930130086	EVO367385H10
<b>85.50mm</b>					<b>-10.0cc</b>	<b>315</b>	<b>8.7</b>	<b>2618</b>	<b>0.236</b>	<b>0.0025</b>	<b>0.0033</b>	<b>929925866</b>	* EVO367366P10*
<b>86.00mm</b>						<b>321</b>	<b>8.7</b>					<b>929925885</b>	* EVO367385P10*
85.50mm	94.0mm	150mm	31.7mm	22mm	-11.9cc	312	8.9	2618	0.236	0.0025	0.0033	930143666	* EVO248366P14*
<b>86.00mm</b>						<b>318</b>	<b>9.0</b>					<b>930143685</b>	* EVO248385P14*
85.50mm	100.0mm	150mm	28.7mm	22mm	-18.6cc	276	8.7	4032	0.236	0.0016	0.0024	930131866	EVO130366H19
86.00mm						282	8.8					930131886	EVO130385H19
85.50mm						280	8.7	2618	0.236	0.0025	0.0033	929990666	* EVO130366P19*
<b>86.00mm</b>						<b>286</b>	<b>8.8</b>					<b>929990685</b>	* EVO130385P19*

\*PowerPak Plus 2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications

**MITSUBISHI 4B11T EVO X 2.0L**

1.2, 1.2, 2.8mm Performance Ring Set Included													
CR calculated at zero deck and 1.02mm head gasket thickness							<b>49cc</b>						
86.00mm	86.0mm	143.75mm	33.37mm	23mm	-4.5cc	331	9.4	2618	0.500	0.0025	0.0033	929945985	* EVO314385P05*
86.50mm						337	9.5					929945905	* EVO314405P05*

\*PowerPak Plus 2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications

**NISSAN SR20DET (SILVIA) 2.0L**

NOTE : Must check oil squirter clearance, possible modification needed.

1.2, 1.2, 2.8mm Performance Ring Set Included													
CR calculated at 0.47mm below deck and 1.09mm head gasket thickness							<b>46.5cc</b>						
86.50mm	86.0mm	136mm	31.83mm	22mm	-11.5cc	309	8.5	4032	0.236	0.0016	0.0024	930101105	NIS253405H42
87.00mm						313	8.6					930101125	NIS253425H42

**NISSAN KA24 DET 2.4L**

NOTE : Must check oil squirter clearance, possible modification needed.

1.2, 1.2, 2.8mm Performance Ring Set Included													
CR calculated at zero deck and 1.02mm head gasket thickness							<b>46cc</b>						
90.00mm	96.0mm	165.0mm	34mm	21mm	-24.0cc	366	9.0	2618	0.236	0.0025	0.0033	929931143	NIS338543H24